

Installation Guide

HANGING INSTRUCTIONS FOR SOURCE ONE EXCLUSIVE TYPE II WALLCOVERING

**STOP - PLEASE CHECK BEFORE CUTTING:
COLOR - CONDITION - QUANTITY - QUALITY
BEFORE CUTTING OR HANGING**

Customer assumes full responsibility for wallcovering after being cut. Before cutting, paper hanger should inspect goods to determine if wallcovering can be installed properly. No claims allowed for more than three strips on the wall.

HANGING INSTRUCTIONS

- 1) Carefully inspect this material for any defects, no credit will be authorized for any reason if defective material is hung.
- 2) Before applying wall covering, prime and prepare walls accordingly.
- 3) Adhesive - use only a quality undiluted premixed vinyl adhesive. Remove any excess adhesive immediately with warm water. If excess paste is not removed, permanent damage could result to the face of the wallcovering.
- 4) When installing a texture wallcovering, reversing alternate strips may help minimize subtle shading caused by the reproduction of natural materials.
- 5) Wallcovering rolls are marked numerically. Please hang in sequence.
- 6) To clean and care for wallcovering, use mild soap and water and a non-abrasive sponge.
- 7) If you have any questions, before proceeding, please contact your local sales representative.
- 8) Walls should be free of dirt, mold and mildew prior to installation. Further, conditions that allow moisture infiltration to get into the walls, should be corrected prior to installation. Consult with professional.
- 9) MYLAR OR MICRO FIBERS: Extra care to be taken not to get any adhesive on the surface as removal can be difficult and damage the product.
- 10) For more hanging instructions, go to www.MyWall.com

CARE AND MAINTENANCE OF WALLCOVERING

Wallcovering requires proper care and maintenance. This will prolong the life of your vinyl wallcovering and maintain its authentic splendour.

The following general cleaning instructions will serve as a guide to normal cleaning maintenance.

1. General Conditions - Day to Day Soil

Ordinary dirt and smudges can be removed with a mild soap and warm water. Gently clean (do not scrub) from bottom of wall upwards using a soft sponge. Rinse with clean water from the top down using a different sponge, this is to ensure all soap is off the wallcovering. Deeply embossed wallcovering needs extra attention in case soap or loosened dirt lodges in depressed surfaces.

Not recommended for cleaning are steel wool, hard bristle brushes or abrasive cleaners because they may damage the surface leaving an unsightly appearance. DO NOT USE active solvent-type cleaners. They will remove print and/or finish from the wallcovering.

Installation Guide

2. Patching and Repairing

Since vinyl wallcovering can be readily peeled off properly prepared walls, patching can be handled in two ways:

(a) Removal of an entire strip

The full-length strip can normally be peeled off the wall. Once removed it can be replaced with a new length.

(b) Removal of a small section (Inlay Method)

Cut around the damaged section of vinyl wallcovering and remove it. A larger patch is then cut from the new material and pasted over the cut-out area so that the pattern matches. The overlap is cut with a new single-edge razor blade through to the wall. The excess material is then removed and the edges of the patch pressed into place. Care should be taken not to score the base wall surface when applied to dry wall construction.

Always use the same run when repairing wallcovering to ensure an exact match. We recommend ordering enough for maintenance when placing the initial order.